




LCE375P - Cell data sheet

Classification

Brand	Alcad
Cell type	LCE375P
Cell P/N	310550451
Capacity at 5 hours rate	375 Ah
IEC Designation	KL375P
According to IEC 60623	



Wiring principle Normal



Physical data

Overall height	413 mm		
Cell height	405 mm		
Width	196 mm	Weight per cell	16,6 Kg
Length	126 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm	Handle	No

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	4,4 liters		

Connection

Cable area of internal connection cables	35 mm²	End-lug (and external cable)	35 mm²
--	--------	------------------------------	--------



LCE375P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,44 mOhm	Short circuit current	3120 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	38,6	47,8	75,0	120	160	193	247	318	357	384	412	473	525	562	675	725
1,05	38,3	47,6	74,2	116	145	166	207	269	298	309	343	392	422	461	554	602
1,1	37,5	46,0	70,6	97,8	123	142	167	210	227	249	274	287	344	375	457	501
1,14	36,7	43,2	62,1	84,8	102	113	130	166	178	184	208	241	280	307	382	422
1,16	34,4	39,4	53,8	72,8	86,8	93,9	107	140	155	168	184	220	256	280	348	385

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	44,8	54,6	83,8	128	167	199	252	322	359	385	413	473	525	562	675	725
1,05	44,6	54,9	84,3	128	157	178	220	285	314	325	361	411	443	484	582	632
1,1	43,8	53,5	81,5	111	138	158	185	232	250	274	301	316	378	413	502	551
1,14	43,0	50,6	72,6	98,1	117	129	149	190	203	210	237	275	320	349	435	481
1,16	40,5	46,3	63,2	85,1	101	109	124	162	180	195	213	255	297	324	404	447



LCE375P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,7	7,85	5,00	3,12	2,34	1,95	1,52	1,18	1,05	0,98	0,91	0,79	0,71	0,67	0,56	0,52
1,05	9,8	7,88	5,05	3,23	2,58	2,26	1,81	1,39	1,26	1,21	1,09	0,96	0,89	0,81	0,68	0,62
1,1	10,0	8,16	5,31	3,83	3,05	2,65	2,25	1,79	1,66	1,51	1,37	1,31	1,09	1,00	0,82	0,75
1,14	10,2	8,68	6,04	4,42	3,69	3,33	2,89	2,26	2,11	2,03	1,81	1,55	1,34	1,22	0,98	0,89
1,16	10,9	9,5	6,98	5,15	4,32	3,99	3,52	2,69	2,41	2,23	2,04	1,70	1,47	1,34	1,08	0,97

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,38	6,87	4,47	2,92	2,24	1,88	1,49	1,17	1,04	0,97	0,91	0,79	0,71	0,67	0,56	0,52
1,05	8,41	6,83	4,45	2,93	2,38	2,11	1,70	1,32	1,19	1,15	1,04	0,91	0,85	0,77	0,64	0,59
1,1	8,55	7,01	4,60	3,39	2,72	2,37	2,02	1,62	1,50	1,37	1,24	1,19	0,99	0,91	0,75	0,68
1,14	8,71	7,41	5,17	3,82	3,20	2,90	2,52	1,98	1,85	1,78	1,58	1,36	1,17	1,07	0,86	0,78
1,16	9,27	8,09	5,94	4,41	3,71	3,43	3,03	2,31	2,08	1,93	1,76	1,47	1,26	1,16	0,93	0,84